



BASIX

Sold as a complete valve

BASIX comes in following combinations:

Manually operated valves:

Type H head w/Tank welding body Type H head w/Pipe welding body Type H head w/Mini Clamp body Type H head w/1" Clamp body

Pneumatically operated valve:

Type N head w/Tank welding body Type N head w/Pipe welding body Type N head w/Mini Clamp body Type N head w/1" Clamp body

Membrane:

Silicone, EPDM, or PTFE

Outlet: W9 Hose Piece (ID 5 mm - OD 14 mm)

Valve seat: ø5 mm

Material contact: AISI 316L (1.4404)

Surface:

 $\begin{array}{ll} \text{Outside:} & \text{Ra} \leq 1.2 \ \mu\text{m} \\ \text{Inside (wetted surface):} & \text{Ra} \leq 0.8 \ \mu\text{m} \\ \text{Process connection:} & \text{Ra} \leq 0.8 \ \mu\text{m} \end{array}$

Pressure: 0-6 bar





4KAI

Heads and bodies sold separately

4KAI comes in following types:

Heads:

Type H, manually operated Type N, pneumatically operated

Membranes: Silicone, EPDM, or PTFE

Bodies:

Tank welding Pipe welding Mini Clamp 1" Clamp

In- and outlet: W9 Hose Piece (ID 5 mm - OD 14 mm)

Valve seat: ø5 mm

Material contact: AISI 316L (1.4404)

Surface:

 $\begin{array}{ll} \text{Outside:} & \text{Ra} \leq 1.2 \ \mu\text{m} \\ \text{Inside (wetted surface):} & \text{Ra} \leq 0.8 \ \mu\text{m} \\ \text{Process connection:} & \text{Ra} \leq 0.8 \ \mu\text{m} \end{array}$

Pressure: 0-6 bar