



HRDLO CLAMP dle normy DIN 32676

DIN 32676	rozměry připojení* Ø A x S	Ø E	C dlouhé K14WL	C* střední K14W	C krátké K14S
DN 4	6,0 x 1,0	25,0	35,0	18,0 (28,0)	12,7
DN 4	6,0 x 1,0	34,0	35,0	18,0 (28,0)	12,7
DN 6	8,0 x 1,0	25,0	35,0	18,0 (28,0)	12,7
DN 6	8,0 x 1,0	34,0	35,0	18,0 (28,0)	12,7
DN 8	10,0 x 1,0	25,0	35,0	18,0 (28,0)	12,7
DN 8	10,0 x 1,0	34,0	35,0	18,0 (28,0)	12,7
DN 10	12,0 x 1 (1,5)	25,0	35,0	18,0 (28,0)	12,7
DN 10	12,0 x 1 (1,5)	34,0	35,0	18,0 (28,0)	12,7
DN 10	12,0 x 1 (1,5)	50,5	35,0	18,0 (28,0)	12,7
DN 10	13,0 x 1,5	25,0	35,0	18,0 (28,0)	12,7
DN 10	13,0 x 1,5	34,0	35,0	18,0 (28,0)	12,7
DN 10	13,0 x 1,5	50,5	35,0	18,0 (28,0)	12,7
DN 15	18,0 x 1,5	25,0	35,0	18,0 (28,0)	12,7
DN 15	18,0 x 1,5	34,0	35,0	18,0 (28,0)	12,7
DN 15	18,0 x 1,5	50,5	35,0	18,0 (28,0)	12,7
DN 15	19,0 x 1,5	25,0	35,0	18,0 (28,0)	12,7
DN 15	19,0 x 1,5	34,0	35,0	18,0 (28,0)	12,7
DN 15	19,0 x 1,5	50,5	35,0	18,0 (28,0)	12,7
DN 20	22,0 x 1,5	34,0	35,0	18,0 (28,0)	12,7
DN 20	22,0 x 1,5	50,5	35,0	18,0 (28,0)	12,7
DN 20	23,0 x 1,5	34,0	35,0	18,0 (28,0)	12,7
DN 20	23,0 x 1,5	50,5	35,0	18,0 (28,0)	12,7
DN 25	28,0 x 1,5	50,5	39,0	21,5 (28,0)	12,7
DN 25	29,0 x 1,5	50,5	39,0	21,5 (28,0)	12,7
DN 32	34,0 x 1,5	50,5	39,0	21,5 (28,0)	12,7
DN 32	35,0 x 1,5	50,5	39,0	21,5 (28,0)	12,7
DN 40	40,0 x 1,5	50,5	39,0	21,5 (28,0)	12,7
DN 40	41,0 x 1,5	50,5	39,0	21,5 (28,0)	12,7
DN 50	52,0 x 1,5	64,0	41,0	21,5 (28,0)	12,7
DN 50	53,0 x 1,5	64,0	41,0	21,5 (28,0)	12,7
DN 65	70,0 x 2,0	91,0	49,0	28,0	15,8
DN 80	85,0 x 2,0	106,0	49,0	28,0	15,8
DN 100	104,0 x 2,0	119,0	49,0	28,0	15,8
DN 125	129,0 x 2,0	155,0	49,0	28,0	-
DN 150	154,0 x 2,0	183,0	49,0	28,0	-
DN 200	204,0 x 2,0	233,5	49,0	28,0	-
DN 250	254,0 x 2,0	268,0	49,0	28,0	-
DN 300	304,0 x 2,0	319,0	49,0	28,0	-

ISO 1127	rozměry připojení* Ø A x S	Ø E	C dlouhé K14WL	C* střední K14W	C krátké K14S
DN 8	13,5 x 1,6 (2,0)	25,0	35,0	18,0 (28,0)	12,7
DN 8	13,5 x 1,6 (2,0)	34,0	35,0	18,0 (28,0)	12,7
DN 8	13,5 x 1,6 (2,0)	50,5	35,0	18,0 (28,0)	12,7
DN 10	17,2 x 1,6 (2,0)	25,0	35,0	18,0 (28,0)	12,7
DN 10	17,2 x 1,6 (2,0)	34,0	35,0	18,0 (28,0)	12,7
DN 10	17,2 x 1,6 (2,0)	50,5	35,0	18,0 (28,0)	12,7
DN 15	21,3 x 1,6 (2,0)	34,0	35,0	18,0 (28,0)	12,7
DN 15	21,3 x 1,6 (2,0)	50,5	35,0	18,0 (28,0)	12,7
DN 20	26,9 x 1,6 (2,0)	50,5	39,0	21,5 (28,0)	12,7
DN 25	33,7 x 2,0	50,5	39,0	21,5 (28,0)	12,7
DN 32	42,4 x 2,0	50,5	39,0	21,5 (28,0)	12,7
DN 32	42,4 x 2,0	64,0	39,0	21,5 (28,0)	12,7
DN 40	48,3 x 2,0	64,0	41,0	21,5 (28,0)	12,7
DN 50	60,3 x 2,0	77,5	43,0	28,0	12,7
DN 65	76,1 x 2,0	91,0	49,0	28,0	15,8
DN 80	88,9 x 2,3	106,0	49,0	28,0	15,8
DN 100	114,3 x 2,3	130,0	49,0	28,0	15,8
DN 125	139,7 x 2,6	155,0	-	28,0	-
DN 150	168,3 x 2,6	183,0	-	28,0	-
DN 200	219,1 x 2,6	233,5	-	28,0	-

ASME BPE	rozměry připojení Ø A x S	Ø E	C dlouhé K14WL	C střední K14W	C krátké K14S
DN 1/4"	6,35 x 0,89	25,0	35,0	21,5	12,7
DN 3/8"	9,53 x 0,89	25,0	35,0	21,5	12,7
DN 1/2"	12,7 x 1,65	25,0	35,0	21,5	12,7
DN 3/4"	19,05 x 1,65	25,0	35,0	21,5	12,7
DN 1"	25,4 x 1,65	50,5	39,0	21,5	12,7
DN 1 1/2"	38,1 x 1,65	50,5	39,0	21,5	12,7
DN 2"	50,8 x 1,65	64,0	41,0	21,5	12,7
DN 2 1/2"	63,5 x 1,65	77,5	43,0	28,0	15,8
DN 3"	76,2 x 1,65	91,0	49,0	28,0	15,8
DN 4"	101,6 x 2,11	119,0	49,0	28,0	15,8
DN 6"	152,4 x 2,77	167,0	-	28,0	-